



RG630



* The EAG30 in the picture is not included.

RG630

Specifications

Physical Characteristics

Dimension	156 (L) * 85 (W) * 156(H) mm
Weight	275g (without terminal)
Electronic Type	Connected with EA630 via pogo pin
Power Input	From EA630
User Input	Trigger

RFID Performance

Standards Supported	EPC Class1 Gen2 V2
RFID Engine	M6e-Micro (RAIN RFID supported)
RFID Chip	Impinj R2000
Read Rate	750 tags/sec
Read Distance	8m (Circular antenna)
Frequency Range	TW: 922-928 MHz US: 902-928 MHz EU: 865-868 MHz Japan: 916-921 MHz CH: 920-924 MHz

Communication

Host Connection	Electrical 6-pin connection
Host Computer	Unitech EA630 mobile computer

User Environment

Drop Specification	1.2m (with terminal)
Operating Temp.	-20 ~ 50°C
Storage Temp.	-30 ~ 60°C
Humidity	5% ~ 90%
Electrostatic Discharge	+/- 15kV air discharge +/- 8kV contact discharge
Sealing	IP52 (with terminal)



Headquarters

Taipei, Taiwan
<http://www.ute.com> e-mail: info@hq.ute.com

unitech America

Los Angeles
<http://us.ute.com> e-mail: info@us.ute.com
<http://can.ute.com> e-mail: info@can.ute.com
Mexico
<http://latin.ute.com> e-mail: info@latin.ute.com

unitech Asia Pacific & Middle East

Taipei
<http://apac.ute.com> e-mail: info@apac.ute.com / info@india.ute.com
<http://mideast.ute.com> e-mail: info@mideast.ute.com

unitech Europe

Tilburg / Netherlands
<http://eu.ute.com> e-mail: info@eu.ute.com

unitech Japan

Tokyo
<http://jp.ute.com> e-mail: info@jp.ute.com

unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen
<http://cn.ute.com> e-mail: info@cn.ute.com
Taipei <http://tw.ute.com> e-mail: info@tw.ute.com

